


SP104 Series Dimension Diagram(unit: mm)



TYPE	A(±0.3)	B(±0.3)	H(±0.3)	D	N	I	J
SP104	9.0	10.0	4.0	2.9	9.5	4.5	2.5

SP104 Series Electrical Characteristics:

PART NO.	L (μH)	L TEST	DCR (Ω)	IDC (A)
	INDUCTANCE	FREQUENCY	MAX	MAX
SP1040-100M	10	2.52 MHZ	0.05	2.38
SP1040-120M	12	2.52 MHZ	0.06	2.13
SP1040-150M	15	2.52 MHZ	0.07	1.87
SP1040-180M	18	2.52 MHZ	0.08	1.73
SP1040-220K	22	2.52 MHZ	0.09	1.60
SP1040-270K	27	2.52 MHZ	0.10	1.44
SP1040-330K	33	2.52 MHZ	0.12	1.26
SP1040-390K	39	2.52 MHZ	0.15	1.20
SP1040-470K	47	2.52 MHZ	0.17	1.10
SP1040-560K	56	2.52 MHZ	0.20	1.01
SP1040-680K	68	2.52 MHZ	0.22	0.91
SP1040-820K	82	2.52 MHZ	0.25	0.85
SP1040-101K	100	1 KHZ	0.34	0.74
SP1040-121K	120	1 KHZ	0.40	0.69
SP1040-151K	150	1 KHZ	0.54	0.61
SP1040-181K	180	1 KHZ	0.62	0.56
SP1040-221K	220	1 KHZ	0.72	0.53

SP1040-271K	270	1 KHZ	0.95	0.45
SP1040-331K	330	1 KHZ	1.10	0.42
SP1040-391K	390	1 KHZ	1.24	0.38
SP1040-471K	470	1 KHZ	1.53	0.35
SP1040-561K	560	1 KHZ	1.90	0.32

Notes:

1, the inductance tolerance: J +5%; K +10%; L +15%; M +20%, customers can choose according to their own conditions, inductance tolerance!

2, if the standard exceeds the requirements of the above, you can also customize the product according to customer's needs!

EASTEVER ELECTRONICS
www.yfbalun.com
Tel:+86-756-8898808

EASTEVER ELECTRONICS
www.yfbalun.com
Tel:+86-756-8898808